

OneWayPro® SEALING TAPE

TECHNICAL DATA SHEET

Description:

OneWayPro® SEALING TAPE is a permanent, long-lasting roll of ultraclear adhesive tape for edge protection of adhesive films.

Specifications:

OneWayPro® SEALING TAPE is recommended for long-term edge protection of self-adhesive films such as OneWayPro® microperforated films. **OneWayPro® SEALING TAPE** provides improved resistance to temperature variations, mechanical peeling and shrinkage.

The film is composed of a 50µ ultraclear cast PVC, an ultraclear solvent adhesive protected by a PET liner. It perfectly follows the relief of the protected edges.

Uses:

OneWayPro® SEALING TAPE can be applied to the edges as well as to the joints between two adhesive films. Particular care should be taken not to apply the tape to the silicone seals on the glass, as the adhesion to the silicone is very poor and the tape may peel off.

Durability:

The durability of the product can go up to 10 years.

Storage:

2 years, between 15 et 25°C and a humidity of 45 to 55% in the original box.

Adherence:

Quick Tack on glass: 15 N / 25 mm +/- 2.5 N / 25 mm (FTM 9)

Tensile strength 180 ° glass after 20 minutes: 11 N / 25 mm +/- 2.5 N / 25 mm (FTM 1)

Tensile strength 180 ° glass after 24 hours: 14 N / 25 mm +/- 2.5 N / 25 mm (FTM 1)

Application temperature: 10 ° to 40 ° C

OneWayPro®

HIGH QUALITY ONE WAY VISION

Operating Temperature: -20 ° C to 80 ° C

Instructions for use :

You will find a file on our website under the tab "Tips for use" with important information for the use of our products.

Product references:

Sealing Tape	50μ	Ultraclear 50μ Sealing Tape	PET Liner	0,01 x 50	SEALING-TAPE-001050
---------------------	------------	--	------------------	------------------	---------------------

Note:

The information contained in this brochure is based on laboratory tests and experience we have gained in practice. They could not provide a legal guarantee. A preliminary test on the material is to be made. Sustainability is estimated from the exposure conditions in Central Europe. The actual life of the product depends on substrate preparation, exposure conditions and maintenance of the marking. We can expect performance degradation outside when the films are exposed to the south, if they are applied in areas where the temperature is often high as countries of southern Europe, or in polluted areas.

Zoning de la Voie Cuivrée, 19
5503 Sorinnes (Belgium)
Mobile : +32 472 466 109
Email : sales@onewaypro.eu